



Instructions for Installation

Cut ties and remove before using gate.

No tools required for assembly.

1. Place the gate in the doorway.

NOTE: Be sure to place the gate so the locking mechanism is on the side of the gate that will be away from the child.

2. Pull top arm up into its open, unlocked position (Fig. 1).
 3. Slide the locking pin to the slot that will extend the gate to match your doorway opening (Fig. 2).
 4. Press top arm down onto the wooden locking bar (Fig. 3). This will secure the gate, under pressure, in the doorway. Do not overload the locking bar during set up. Keep this top locking bar in line with the bottom locking bar while applying pressure. It is normal for the vertical side boards to flex and bow slightly.
- CAUTION:** Avoid forcing the locking bar into position. Minimal pressure should be used to seat top arm.
5. Check that the gate is secure in the doorway by gently pulling on the top of the gate. If the gate moves, repeat steps 2, 3 and 4 until you find the right slot to secure the gate properly.
 6. To open the gate, simply pull up on top arm, and lift the gate up and away from the doorway.

Care and Maintenance

To clean: wipe with a clean, soft, damp cloth and dry thoroughly. Do not use harsh or abrasive cleaners.

DO NOT IMMERSE THE GATE IN WATER. Always keep the pressure pad bumpers clean.