



"No-Pull" solution


TERMS FOR FITTING INSTRUCTIONS



Strap in Leash Position



Strap in "No-Pull" Solution Position



Fitting Instructions

Note: Use With Standard Collars

READ BEFORE USING YOUR THUNDERLEASH

While the use of a ThunderLeash in the "no pull" configuration applies much less pressure on the neck than connecting directly to a standard collar, the "no-pull" configuration does not eliminate all pressure on the neck or trachea. If your dog shows any signs of distress from pressure on the neck when using a ThunderLeash, stop use and contact us. If your dog has a sensitive neck or trachea, we do not recommend using a ThunderLeash.



1. Clip ThunderLeash onto your dog's collar and slide the leash strap into the **"No-Pull" Solution Position**. Wrap the ThunderLeash around your dog's torso and slide the leash into the **"No-Pull" Solution Slot** on the hardware.
2. Adjust the **Slack Buckle** until ThunderLeash stays loosely against your dog's torso without tension on the leash.

You should be able to easily slide two fingers between the leash and your dog's chest when your dog is not pulling.

3. The **Safety Buckle** prevents too much pressure from being applied when dog pulls.

Follow guidelines in the Buckle Adjustments table below to position the Safety Buckle properly. Adjust as needed.

BUCKLE ADJUSTMENTS

Approximate. Adjust as needed.

WEIGHT	LEASH SIZE	Distance Between Safety Buckle and Slack Buckle
< 12 lbs	XS	~1-1.5 inches
12 - 25 lbs	S	~1.5-2 inches
26 - 100 lbs	M/L	~2.5 inches
> 100 lbs	M/L	~3 inches